

SECTION 1 - MANUFACTURER INFORMATION

.....

MANUF/DIST : CHEM-POWER MFG DIV/ FOSTER & CO., INC
15 Wing Drive EMERGENCY PHONE.....: 973-267-4100
Cedar Knolls PREPARATION/REVISION DATE: 02/14/02
NJ 07927
PREPARER/CONTACT: Gary Adams, Chemist
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: EZ-LIFT (Aerosol)
CHEMICAL NAME/SYNONYMS: Gasket Remover
CHEMICAL FAMILY.....: Chlorinated Solvent Solution
FORMULA.....: Complex Mixture
PRODUCT CODE.....: 19-77

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

*
* HEALTH..... 2 *
* FLAMMABILITY.. 2 *
* REACTIVITY.... 0 *
* PROTECTION.... B *

SECTION 2 - HAZARDOUS INGREDIENTS

.....

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

| CHEMICAL/COMMON NAME | CAS-NUMBER | % | PEL-OSHA | TLV-ACGIH |
|--|------------|-----|----------|-----------|
| **Methylene Chloride (Dichloromethane) | 75-09-2 | 79 | 25 PPM | 25 PPM |
| **Methanol | 67-56-1 | 5-8 | 200 ppm | 200 ppm |
| **Ammonium Hydroxide 26 Be | 1336-21-6 | 3-5 | N/I | 50 PPM |
| Isobutane (Propellant) | 75-28-5 | 5 | N/I | 1000 ppm |
| Nonylphenoxypolyethoxyethanol | 26027-38-3 | 2-6 | N/I | N/I |
| **Toluol | 108-88-3 | 3 | 200 ppm | 100 ppm |
| Hydroxypropyl methylcellulose | 9004-65-3 | <2 | N/I | 10mg/m3 |
| Paraffin Wax (TLV as oil mist) | 64742-43-4 | <2 | N/I | 5mg/m3 |

**this ingredient is reportable under EPA SARA Title 111-please check applicable states for additional regulations.

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):YES

| CHEMICAL/COMMON NAME | CAS-NUMBER | % | NTP | IARC | OSHA |
|----------------------|------------|-------|-----|------|------|
| Methylene Chloride | 75-09-2 | 75-80 | Yes | Yes | No |

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute And Chronic)-

ACUTE: INHALATION: Overexposure may cause symptoms of central nervous system depression ranging from **dizziness, light-headedness** to unconsciousness/death in severe cases. SKIN: Moderate skin irritant, can cause burns from excess defatting of the skin. EYES: Severe irritant causes severe pain and general inflammation with possible permanent damage. INGESTION: Can cause gastric distress and possible CNS depression from absorbed product. CHRONIC: Headaches, mental confusion, fatigue, visual disturbances are possible from chronic inhalation exposure. Severe dermatitis can occur from prolonged overexposure to the skin. Concerning the Methylene Chloride Fraction Note from Section 2: A 1985 animal inhalation study report states that there is "clear evidence of carcinogenicity" in mice and female rats. Experience in industry has shown no increased incidences of cancer of any type in the worker population. IARC lists Methylene Chloride as having inadequate evidence in humans and adequate evidence as an animal carcinogen. NTP lists it as "clear evidence" mouse and rat but evidence to date suggests this as a result of a different metabolism chain from humans.

PRIMARY ROUTES OF ENTRY-

Inhalation, skin contact, eye contact, skin exposure, ingestion,

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-

Persons with Angina and/or history of heart problems should not be exposed to this product. Methylene Chloride is a possible is a possible carcinogen based on incomplete evaluation. Exposure limit should be 50ppm average for 8 hour day.

EMERGENCY FIRST AID PROCEDURES-

EYES: Immediately flush with plenty of water for at least 15 minutes, holding eyelids apart to ensure flushing the entire eye surface. Seek medical attention IMMEDIATELY. SKIN: Wash with plenty of mild soap and water. Remove contaminated clothing and launder before reuse. Consult physician if irritation persists. IF SWALLOWED: Induce vomiting, but try to keep the persons head below his hips to prevent aspiration of fluid into the lungs while vomiting. Give warm water and repeat until vomit fluid is clear. Give two teaspoons of baking soda in a glass of water. Call physician or poison control center immediately.

SECTION 4 - CHEMICAL DATA

| | |
|-------------------------------|---------------------------------------|
| BOILING POINT (F).....: 113 F | SPECIFIC GRAVITY (WATER=1).....: 1.25 |
| VAPOR PRESSURE (mmHg): N/I | PERCENT VOLATILE BY VOLUME (%): 96 |
| VAPOR DENSITY (AIR=1): >1 | EVAPORATION RATE (water =1): <1 |

SOLUBILITY IN WATER-
Appreciable.

APPEARANCE AND ODOR INFORMATION-

Viscous liquid in aerosol with aromatic and ammoniacal odor.

SECTION 5 - PHYSICAL HAZARD DATA

EXTINGUISHING MEDIA-
Dry Chemical, water fog, Carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES-
Use water spray to keep containers cool. Wear self-contained breathing gear.

UNUSUAL FIRE AND EXPLOSION HAZARDS-
Flammable by CPSC Flame Extension Test. Cans exposed to temperatures above 130 degrees F can explode from gas pressure build-up.

INCOMPATIBILITY (Materials To Avoid)-
Pure Oxygen, alkali metals, open flames and electrical arcs.

HAZARDOUS DECOMPOSITION PRODUCTS-
Hydrogen Chloride vapor and minor amounts other toxic gases,ie. Phosgene.

WILL HAZARDOUS POLYMERIZATION OCCUR-
No.

CONDITIONS TO AVOID FOR POLYMERIZATION-
None known.

IS THE PRODUCT STABLE-
Yes.

CONDITIONS TO AVOID FOR STABILITY-
Elevated temperature, keep below 120 F.

SECTION 6 - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED-
Dike and contain spill. Provide adequate ventilation. Soak up with absorbent and place in metal containers for proper disposal. All rinsate should be contained and placed in approved containers for proper disposal. Spills on dirt, grass, etc. can be cleaned up by removing contaminated dirt and placing it in containers for proper disposal. Cleanup personnel should wear adequate protective equipment.

WASTE DISPOSAL METHODS-
The materials resulting from clean-up may be hazardous wastes. Package, store, transport and dispose of all related matter in accordance with prevailing federal, state and local health and environmental regulations. Use approved, qualified waste removal contractors. Empty cans should be evacuated to ambient pressure, wrapped in paper for disposal in industrial waste. NEVER PUNCTURE, INCINERATE OR ATTEMPT TO RE-USE AEROSOL CONTAINERS.

SECTION 7 - EXPOSURE CONTROL INFORMATION

VENTILATION-
LOCAL EXHAUST: Good
SPECIAL.....: N/A
MECHANICAL (General): away from work area
OTHER.....: N/A

RESPIRATORY PROTECTION-

Never enter a tank or confined area without air-supplied respirator.

PROTECTIVE GLOVES-

Polyfluorinated polyethylene or cloth with frequent changes when penetrated.

OTHER PROTECTIVE EQUIPMENT-

Splash-proof goggles.

OTHER ENGINEERING CONTROLS-

N/I

WORK PRACTICES-

Do work with the best ventilation available.

HYGIENIC PRACTICES-

Wash hands BEFORE using lavatory facilities when using this product.

SECTION 8 - SPECIAL PRECAUTIONS

.....

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE-

Temperatures above 130 F may cause cans to explode. Keep boxes and cans dry.

MAINTENANCE PRECAUTIONS-

N/I

OTHER PRECAUTIONS-

KEEP OUT OF REACH OF CHILDREN!

ADDITIONAL COMMENTS-

SHIPPING NAME: Consumer Commodity ORM-D.

AIR TRANSPORT of this product is PROHIBITED.

FOR TRANSPORTATION EMERGENCY CALL INFOTRAC 1-800-535-5053, 24 hrs/7 days.