

SECTION 1 - MANUFACTURER INFORMATION

MANUF/DIST : CHEM-POWER MFG DIV/ FOSTER & CO., INC
15 Wing Drive EMERGENCY PHONE.....: 973-267-4100
Cedar Knolls PREPARATION/REVISION DATE: 03/18/03
NJ 07927
PREPARER/CONTACT: Gary Adams, Chemist
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: GLISTEN TIRE AND VINYL SHINE
CHEMICAL NAME/SYNONYMS: Silicone/Wax Polish (AEROSOL)
CHEMICAL FAMILY.....: Emulsion
FORMULA.....: Silicone Polymer Emulsion
PRODUCT CODE.....: 19-20

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

* * * * *
* HEALTH..... 1 *
* FLAMMABILITY.. 1 *
* REACTIVITY.... 0 *
* PROTECTION.... B *
* * * * *

SECTION 2 - HAZARDOUS INGREDIENTS

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

CHEMICAL/COMMON NAME	CAS-NUMBER	%	PEL-OSHA	TLV-ACGIH
Water	7732-18-5	>60	N/I	N/I
Dimethylpolysiloxane	63148-62-9	6-18	N/I	N/I
Poly(oxyethylene)/decyl Ether	26183-52-8	1-10	N/I	N/I
Butane	106-97-8	2-8	800 ppm	800 ppm
Propane	74-98-6	2-8	2500 ppm	2500 ppm

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):NO

CHEMICAL/COMMON NAME	CAS-NUMBER	%	NTP	IARC	OSHA
None listed	N/A	N/A	N/A	N/A	N/A

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute And Chronic)-
Minor eye irritation possible.

PRIMARY ROUTES OF ENTRY-
Eyes.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-
None known.

EMERGENCY FIRST AID PROCEDURES-

In case of eye contact, flush with water for 15 minutes. Call physician if any irritation persists.

If swallowed: Consult physician.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F).....: 212 SPECIFIC GRAVITY (WATER=1).....: 0.91
VAPOR PRESSURE (mmHg): 43psi PERCENT VOLATILE BY VOLUME (%): >90
VAPOR DENSITY (AIR=1): 4.0 EVAPORATION RATE (water =1): 1

SOLUBILITY IN WATER-
Appreciable, pH=8.96

APPEARANCE AND ODOR INFORMATION-
White liquid, slight sour odor in aerosol can.

SECTION 5 - PHYSICAL HAZARD DATA

FLASH POINT (Method Used): Non-flam FLAMMABLE LIMITS : Lel=1.9 UEL=8.5

EXTINGUISHING MEDIA-
Any. This product will not burn under normal conditions.

SPECIAL FIRE FIGHTING PROCEDURES-
Keep cans cool to avoid bursting.

UNUSUAL FIRE AND EXPLOSION HAZARDS-
Exposure to temperatures above 120F can cause cans to burst explosively.
EXTREMELY FLAMMABLE BY CPSC FLAME EXTENSION TEST. AVOID SPRAYING NEAR FLAME
AND/OR IGNITION SOURCES.

INCOMPATIBILITY (Materials To Avoid)-
None known.

HAZARDOUS DECOMPOSITION PRODUCTS-
In a fire, Silicone Dioxide, Formaldehyde, Carbon Dioxide.

WILL HAZARDOUS POLYMERIZATION OCCUR-
No.

CONDITIONS TO AVOID FOR POLYMERIZATION-
None known.

IS THE PRODUCT STABLE-
Yes.

CONDITIONS TO AVOID FOR STABILITY-
Store in dry place to avoid rusting of cans.

