

SECTION 1 - MANUFACTURER INFORMATION

MANUF/DIST : CHEM-POWER MFG. DIV/ FOSTER AND COMPANY, INC.
15 Wing Drive EMERGENCY PHONE.....: 973-267-4100
Cedar Knolls PREPARATION/REVISION DATE: 02/14/02
NJ 07927
PREPARER/CONTACT: Gary Adams, Chemist
LOCATION : Whs 1

TRADE NAME/SYNONYMS...: QUIK-FIX (Part 2 of 2 MSDS)
CHEMICAL NAME/SYNONYMS: 2 Part Epoxy Patch System/5 Minute Cure
CHEMICAL FAMILY.....: Mercaptan Terminated Polymer/Amine
FORMULA.....: Complex Mixture (Hardener)
PRODUCT CODE.....: 514-206

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS)

* * * * *
* HEALTH..... 1 *
* FLAMMABILITY.. 0 *
* REACTIVITY.... 1 *
* PROTECTION.... B *
* * * * *

SECTION 2 - HAZARDOUS INGREDIENTS

THIS PRODUCT CONTAINS HAZARDOUS INGREDIENTS : YES

CHEMICAL/COMMON NAME	CAS-NUMBER	%	PEL-OSHA	TLV-ACGIH
Mercaptan Polymer	N/I	85-95	None est	None est
Tris (Dimethyl Amino Methyl) Phenol	90-72-3	5-15	None est	None est

THIS PRODUCT CONTAINS CARCINOGENS (NTP, IARC, or OSHA):NO

CHEMICAL/COMMON NAME	CAS-NUMBER	%	NTP	IARC	OSHA
N/A	N/A	N/A	N/A	N/A	N/A

SECTION 3 - HEALTH HAZARD DATA

HEALTH EFFECTS (Acute And Chronic)-
Ingestion: Slightly toxic. No specific information available.
Skin Contact: Irritating to the skin.
Eye Contact: Severely irritating to eyes. May cause permanent injury.
Inhalation: Overexposure can cause irritation of respiratory tract, drowsi-
ness, headache, and nausea.
Chronic Effects of Overexposure: Can be absorbed through skin. Can cause skin
sensitization and dermatitis.
NOTE: As provided by Foster and Company in a small, closed, two part system,
it is unlikely that anyone can accidentally be over-exposed to either part or

the mixture.

PRIMARY ROUTES OF ENTRY-
Skin, eyes, inhalation.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE-
N/I

EMERGENCY FIRST AID PROCEDURES-

EYE Contact: Flush with plenty of water for at least 15 minutes and seek medical attention.

SKIN Contact: Remove contaminated clothing and wash contact area with soap and water for 15 minutes.

INHALATION: In case of exposure to a high concentration of vapor or mist, remove person to fresh air. Get medical attention.

INGESTION: If appreciable quantities are swallowed, seek medical attention. Do not induce vomiting. If vomiting should occur spontaneously, keep airway clear.

SECTION 4 - CHEMICAL DATA

BOILING POINT (F).....: N/I	SPECIFIC GRAVITY (WATER=1).....: 1.15
VAPOR PRESSURE (mmHg): N/I	PERCENT VOLATILE BY VOLUME (%): 0
VAPOR DENSITY (AIR=1): N/I	EVAPORATION RATE (N-Butanol =1): <1

SOLUBILITY IN WATER-
Negligible.

APPEARANCE AND ODOR INFORMATION-
Clear viscous liquid. Sulfur odor.

SECTION 5 - PHYSICAL HAZARD DATA

FLASH POINT (Method Used): >260F FLAMMABLE LIMITS : Lel=N/A UEL=N/A

EXTINGUISHING MEDIA-
Use carbon dioxide or dry chemical for small fires; aqueous foam or water for large fires.

SPECIAL FIRE FIGHTING PROCEDURES-

Wear self-contained breathing apparatus and complete personal protection equipment. Remove all ignition sources Use a water spray to cool fire exposed containers.

UNUSUAL FIRE AND EXPLOSION HAZARDS-

Closed containers may rupture (due to buildup of pressure) when exposed to extreme heat.

INCOMPATIBILITY (Materials To Avoid)-

Strong oxidizing agents and reducing agents. Uncontrolled mixing in masses greater than 1/2 inch thick.

HAZARDOUS DECOMPOSITION PRODUCTS-

Fumes produced when heated to decomposition may include: carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen sulfide and oxides of sulfur.

WILL HAZARDOUS POLYMERIZATION OCCUR-

Will not occur.

CONDITIONS TO AVOID FOR POLYMERIZATION-

Excessive heat.

IS THE PRODUCT STABLE-

Yes.

CONDITIONS TO AVOID FOR STABILITY-

Excessive heat.

SECTION 6 - SPILL OR LEAK PROCEDURES
.....

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED-

Dike spill. Absorb with inert material and collect for disposal. Flush area with water. Prevent washings from entering waterways.

WASTE DISPOSAL METHODS-

Incinerate or use biological treatment in accordance with federal, state and local regulations. This material is not defined as a hazardous waste under current RCRA regulations.

SECTION 7 - EXPOSURE CONTROL INFORMATION
.....

VENTILATION-

LOCAL EXHAUST: maintain TLV

SPECIAL.....: N/A

MECHANICAL (General): maintain TLV

OTHER.....: N/A

RESPIRATORY PROTECTION-

Wear a properly fitted NIOSH/OSHA approved respirator whenever exposure to vapor/mist is likely unless levels are below applicable limits.

PROTECTIVE GLOVES-

For operations where contact can occur, wear impervious gloves (neoprene).

OTHER PROTECTIVE EQUIPMENT-

For operations where contact can occur, coveralls, apron and rubber foot coverings are recommended. A safety shower and eye wash should be available. Chemical splash goggles.

OTHER ENGINEERING CONTROLS-

N/I

WORK PRACTICES-

Apply only in well ventilated areas. Avoid skin contact, wash after using.

HYGIENIC PRACTICES-

Wash hands before eating or using lavatory facilities.

SECTION 8 - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE-

Avoid contamination of skin. Remove and thoroughly launder contaminated clothing before reuse. Discard contaminated shoes.

MAINTENANCE PRECAUTIONS-

N/I

OTHER PRECAUTIONS-

KEEP OUT OF REACH OF CHILDREN!

ADDITIONAL COMMENTS-

Shipping Name: Not regulated. Manufacturer's ID: 04-2385201.
See MSDS 00257 for part 1 of 2 MSDS for product 514-206.